

Thread Lubricants and Waxes



			
PRODUCT	TORQUE TIP®	NYTORQ®	WAXTIP
PRODUCT NUMBER	28		402
MATERIAL	PTFE	PTFE	Wax
COLOUR	YELLOW	YELLOW	Lt BLUE
REUSABILITY	YES	YES	YES
SPECIFICATIONS	SEE NOTE 'A/B'	SEE NOTE 'B'	SEE NOTE 'C'
PATCH STYLE - STD LENGTH	0.12 - 0.17	0.25 - 0.28	0.25 - 0.28
TORQUE TENSION RELATIONSHIP	0.1 TO 0.12	0.1 TO 0.12	0.1 TO 0.12
ON PART LIFT AMBIENT TEMP	>2 YEARS	>2 YEARS	>2 YEARS

These materials are able to meet the requirements of;	
Note 'A'	FORD WSS-M21P17-A4 (XD) FORD WSS-M21P19-A8 & A9'
Note 'B'	FORD WSS-M21P17-A4 (XD)
Note 'C'	FORD WSS-M9G20-B3 GM 9986167

The materials shown here are only a small section of the range that Inlex Locking offers.

For further information please contact one of our application engineers who will be able to offer advice on the correct solution.

FEATURE	CHARACTERISTICS
Torque Tip 28®	A dry, highly lubricative water based film developed specially for thread forming screws. Non-toxic, can be coloured for identification.
Nytoq®	NYTORQ is a film-forming synthetic wax lubricant to coat threaded parts. It is a physiologically harmless precoat to reduce friction and prevents cold welding and can be used in a wide variety of industrial and manufacturing applications. It is also specially designed for self-taping threads. The dried film is dry-to-touch.
WaxTip 402	402 Wax is a microcrystalline wax formulated specifically to reduce drive torques in self-tapping screw applications. 402 is a solid wax compound that contains no VOCs or HAPs, making it the most environmentally friendly torque-friction reducer available. The material is designed to fluoresce under UV light for ease of identification in automated processing systems

Information presented in this data sheet is considered reliable, but conditions and methods of use, which are beyond our control, may modify results. Before these product are used, the user should confirm their suitability.
We cannot accept liability for any loss, injury or damage which may result from its use.
We do not warranty the accuracy or completeness of any such information whether orally or in writing.
We reserve the right at anytime and without notice to update or improve products and processes and our information concerning the same.
Nytorq is a registered trade mark of Nylok LLC
Torque- Tip 28 is a registered trade mark of Inlex Locking ltd
S29.1.2



Inlex Locking Ltd

Wood Lane, Fordhouses, Wolverhampton WV10 8HN
tel: 01902 397300 fax: 01902 785372
enquiries@anochrome-group.co.uk
www.anochrome.co.uk